Drone photogrammetry in surveying

Zach Hoover, Ph.D, B.Sc., B.Geom., Candidate Member—ANSLS Spring seminar, May 30, 2025

Inn on Prince Hotel and Conference Centre, 437 Prince Street, Truro

Overview

- Photogrammetry drones
- Basic workflow
- Best practices
- Examples
- Regulations

Photogrammetry drones

- Fixed Wing
 - Pros—cover large areas quickly and efficiently, long run times
 - Cons—may require runway, cost
- Multi-rotor
 - Pros—maneuverability, ease of use, cost
 - Cons—shorter flights, lower speed



https://aeromao.com/products/vtnaut/



https://store.dji.com/ca/product/dji-mavic-3e-and-dji-care-enterprise-basic?vid=120171




https://www.pegasusaero .ca/g15-sentinel

Photogrammetry drones cont.

- Recommended equipment
 - RTK/PPK
 - Mechanical shutter
- Examples
 - DJI Mavic 3E
 - \$4805.00 (drdrone.ca, drone only)
 - DJI Matrice 300
 - \$13393.00 (drone w/ RTK)
 - \$9099.00 (P1 camera)
 - Many others

Basic workflow

- Mission planning
- GCPs
 - RTK/PPK vs GCPs only
- Flying
- Processing
 - Buy once, cry once
 - Agisoft Metashape, Pix4D (some), DJI Terra
 - Pay per use/recurring
 - Carlson PhotoCapture, DroneDeploy, VirtualSurveyor
 - Free
 - WebODM, Reality Capture
- CAD import




https://a.co/d/aiPrLcY

Best practices


- Mission planning
 - GSD (ground sample distance)
 - Linear distance on the ground covered by one pixel
 - Related to camera focal length, pixel size, and flight height

•
$$H = f \frac{GSD}{pixel \ size}$$

- Very generally,
 - Horizontal relative accuracy = 1-2 * GSD
 - Vertical relative accuracy = 1-3 * GSD
- Flight height is a trade-off
- Flight line overlap
 - ~80% endlap
 - ~50% sidelap



Approximately 60% endlap



GGE4313 notes, Professor Jabari

Best practices

- Environmental
 - Time of day
 - Weather
 - Space weather
 - Time of year
- Safety



https://www.shutterstock.c om/image-vector/unstablecliff-edge-warning-signvector-1997779286



https://www.coverdrone.com/10-tips-for-preventing-drone-crashes/

Examples


















































DTM1, drone




DTM2, drone




	Measurements (m)									Height comparisons (m)				
point	Е		N	H_field	H_dtm1	H_dtm2	description		dtm1 v field	dtm2 v field	dtm1 v dtm2			
	1	24600060.710	5109971.172	6.341	6.395	6.366	parking lot		0.055	0.026	0.029			
	2	24600108.530	5110010.210	6.876	6.838	6.857	parking lot		-0.038	-0.019	-0.019			
	2	24600007 220	F10003F 130	0.463	0.543	0.513	mauliina lak		0.040	0.040	0.000			
	3	24600097.220	5109925.129	9.462	9.512	9.512	parking lot		0.049	0.049	0.000			
	4	24600141.680	5109952.960	12.185	12.102	12.104	parking lot		-0.083	-0.081	-0.002			
	5	24600160.760	5109905.681	14.779	14.963	14.963	slopepaved		0.184	0.184	0.000			
	6	24600116.490	5109906.163	13.120	12.298	12.298	slope		-0.822	-0.822	0.000			
	7	24600142.640	5109900.276	13.704	13.212	13.212	slope		-0.493	-0.493	0.000			
	8	24600172.910	5109911.022	14.947	15.365	15.365	slope		0.418	0.418	0.000			
	9	24600116.500	5109976.581	9.626	9.613	9.609	slope		-0.013	-0.018	0.005			
	10	24600158.790	5109933.087	13.148	13.538	13.408	tree cover		0.390	0.260	0.131			



				Height comparisons (m)							
point	ı	E	N	H_as_measured	H_field	H_dtm1	H_dtm2	description	dtm1 v measured	dtm2 v measured	dtm1 v dtm2
	101	24600061.997	5109967.208	6.471	6.471	6.531	6.541	pl	0.060	0.070	-0.011
	102	24600100 607	5110005.013	6.964	6.964	6.995	7.004	nl	0.031	0.039	-0.008
	102	24000108.087	5110005.013	6.964	0.904	0.995	7.004	ρı	0.031	0.039	-0.008
	103	24600086.865	5109936.521	7.916	7.916	8.000	8.000	pl	0.084	0.084	0.000
	104	24600106 684	5109926.822	10.379	10.379	10.400	10.400	nl	0.021	0.021	0.000
	104	24000100.004	3109920.622	10.579	10.579	10.400	10.400	ρi	0.021	0.021	0.000
	105	24600161.769	5109906.666	14.836	14.836	14.897	14.897	slopepaved	0.061	0.061	0.000
	106	24600113.703	5109905.460	13.549	13.549	13.709	13.674	slone	0.160	0.125	0.035
	100	24000113.703	3103303.400	13.549	13.549	13.709	13.074	siope	0.100	0.123	0.033
	107	24600139.840	5109902.657	12.760	12.760	12.858	12.858	topo	0.098	0.098	0.000
	108	24600177 276	5109919.191	14.496	14.496	14.648	14.669	clana	0.152	0.173	-0.021
	100	24000177.270	5109919.191	14.490	14.490	14.040	14.009	siope	0.132	0.173	-0.021
	109	24600118.871	5109975.955	10.099	10.099	10.192	10.209	topo	0.093	0.110	-0.017
	110	24600138.577	5109938.973	12.558	12.558	12.652	12.644	building_edge	0.094	0.086	0.008



Measurements (m)									Height comparisons (m)					
point	E	N	H_as_measured	H_field	H_dtm1	H_dtm2	description	field v measured	dtm1 v measured	dtm2 v measured	dtm1 v dtm2	closest to measured		
	501 24600107.491	L 5109975.704	7.874	8.231	7.964	7.977	⁷ pl	0.357	0.090	0.103	-0.013	drone		
	502 24600087.024	1 5109941.144	7.726	7.803	7.793	7.793	3 pl	0.077	0.067	0.067	0.000	drone		
	503 24600093.457	7 5109935.489	8.173	8.631	8.312	8.312	2 pl	0.458	0.139	0.139	0.000	drone		
	504 24600101.666	5109928.751	9.651	9.777	9.741	9.741	L pl	0.126	0.090	0.090	0.000	drone		
	505 24600121.563	3 5109962.907	11.630	11.219	11.716	11.716	Spl	-0.411	0.086	0.085	0.001	drone		
	506 24600134.949	9 5109975.628	11.575	11.292	11.675	11.678	3 pl	-0.283	0.100	0.103	-0.004	drone		
	507 24600157.895	5 5109964.069	12.214	12.248	12.247	12.287	storm	0.034	0.033	0.073	-0.040	field		
	508 24600154.260	5109928.985	13.201	. 12.974	12.793	12.948	Bboc	-0.227	-0.408	-0.253	-0.155	none		
	509 24600184.053	3 5109931.749	15.103	15.045	15.105	15.114	foc	-0.059	0.002	0.011	-0.009	drone		
	510 24600165.424	1 5109908.842	14.050	14.671	14.213	14.213	3 pl	0.621	0.163	0.163	0.000	drone		



DTM1, drone



DTM2, drone

Regulations

- Transport Canada
 - https://tc.canada.ca/en/aviation/drone-safety/learn-rules-you-fly-your-drone-safely-legally
 - Updated regulations: November 4, 2025
- Microdrones (under 250g)
- Most photogrammetry drones (250g 25kg)
 - Registration required
 - Pilot certificate required
- Drones over 25kg
 - Special permission required from TC
- Fines for non-compliance

Regulations—licenses

- Basic operations
 - Uncontrolled airspace
 - > 100' horizontally from bystanders
 - > 3 nautical miles from airports/aerodromes
 - > 1 nautical mile from helipads
 - Drone must remain in VLOS
 - Requirements for
 - Recency (24 months)
 - SOP
 - Flight logs
 - Online test


Regulations—licenses

- Advanced operations
 - Assuming approved RPAS model and permission, where required
 - Within controlled airspace
 - Within 3 nautical miles of airports
 - Within 1 nautical mile of heliports
 - Within 5m of bystanders
 - BVLOS with permission
 - Online test + In-person flight review test

Regulations—locations

• Drone site selection tool

https://nrc.canada.ca/en/drone-tool/



Questions?

